



Smarter Charging, Easier Life



Optional Connector Type
J1772(Type1) and Type2 connector and cable provided; support for all new EV models.



Screen Display
Equipped with LCM screen to clearly display charging information.



Delay Charge
Free to set 1/2/4/8hr automatic delay charging, choose cheap electricity price.



Color Light Bar
Convenient for car owners to know the charging state from a distance.



Winding Groove Design
Stored the charging gun and wiring neatly for your convenience.



Maintenance Hole Design
No need to dismantle the whole machine for maintenance.



Emergency Button
Stop charging at any time according to special circumstances.



High Standard Safety Protection
When abnormal condition is detected, power will be cut off automatically.

Application Place



Car Parks



Residential Area



Restaurants and Hotels



Office Buildings



Tourist Attractions



Vehicle Fleets

Specification						
			CBDA-X50A	CBDA-X80A	CBDA-X32B	CBDA-X70B
	Input	Voltage Range	AC 220±10%	AC 220±10%	AC 220±10%	AC 220±10%
		Frequency Range	single phase60Hz	single phase60Hz	single phase 60Hz	single phase 60Hz
		Input Current	50A	80A	32A	70A
		Input Power Connect	L, N, GROUND	L, N, GROUND	L, N, GROUND	L, N, GROUND
	Output	Voltage Range	AC 220±10%	AC 220±10%	AC 220±10%	AC 220±10%
		Frequency Range	60Hz	60Hz	60Hz	60Hz
		Input Current	50A	80A	32A	70A
		Input Power Connect	11kW	17.6kW	7.04kW	15.4kW
	Physical Specification					
	Connector Type	SAE J1772 (Type1)			Type2	
	Cable Length	17 FT (5.1M)				
	Enclosure Dimension (H*W*D)	H 393.9*W 338.7*D 144.4 (mm) (donot including stand)				
	Weight	8.6 (KG)				
User Interface						
	Button	Multi-function Button`Emergency Button`Delay Button/Info Button				
	Indicator Light	● Standby: Green ● Charging: Blue ● Complete: Flashing Green ● Fault: Red				
	User Identification	RFID (MIFARE CARD)				
	LCM Screen	English				
Protection						
	Over-voltage Protection, Over-current Protection, Short-circuit protection,Leakage protection, Overload protection,Surge protection					
Environmental						
	Operating Temperature	-25°C to +50°C				
	IP	IP 55				
	Humidity	<95%				
Standard Compliance						
	Standard	CNS15511				
	Communications	Wi-Fi / RJ45 Ethernet				

- Specifications may be changed as a result of innovation and improvement and further notice may not be given.
- The delay charging of the equipment depends on vehicle models.

- **Model:** CBDA-X80A
- **Serial Model:** CBDA-X80-A4\CBDA-X80-A7\CBDA-X70A\CBDA-X50A\CBDA-350A\CBDA- X50A-A4\CBDA-X50A-A6\CBDA-X50A-A7\CBDA-X40A\CBDA-X40A-A6\CBDA- X32A\CBDA-X32A-A6\CBDA-X24A\CBDA-X24A-A6\CBDA-X16A\CBDA-X16A-A6\CBDA-X70B\CBDA-X70B-A4\CBDA-X70B-A7\CBDA-X50B\CBDA-X40B\CBDA-X32B\CBDA-X32B-A4\CBDA-X32B-A7\CBDA-X24B\CBDA-X16B



單位/mm

